CBS Maxi-Vac TOUGH DUTYM **POWER/VAC® REPLACEMENT**





CBS MaxiVac's™ new Tough Duty™ line of roll-in replacement circuit breakers replaces aging Power/Vac® breakers without

any modifications to existing cells or switchgear. The Tough Duty™ breakers are tested per ANSI/IEEE certification standards, are available in all standard ratings, and include the newest encapsulated pole assemblies from Vacuum Interrupters, Inc. Encapsulated poles harden your breakers against environmental contamination, extending the life of your power distribution equipment.



TOUGH DUTY™ ADVANTAGES

- Direct Roll-In Replacement
- Meets or Exceeds ANSI/IEEE **Testing Standards**
- 5-year, 3,000-Operation Warranty
- New Rugged Encapsulated Vacuum Interrupter Pole Design
- Mechanism Made In USA
- Extended Warranties Available
- Utilizes Trusted ML-17 and ML-18 Mechanisms

CircuitBreaker.com/ToughDuty





CBS Maxi-Vac





Contact your local Group CBS Office or call (800) 232-5809.

Tough Duty™ Power/Vac® Replace

CBS Maxi-Vac Tough Duty™ Power/Vac® Replacement

ADVANTAGES & BENEFITS

Direct Roll-In Replacement	Roll-in replacement requires no cell or wiring modifications, avoiding switchgear replacement and downtime costs.
ANSI/IEEE C ₃₇ Tested	The circuit breaker has been tested to the latest applicable ANSI/IEEE C ₃₇ standards, including C ₃₇ .09.
Mechanism Made In USA	Trusted ML-17 and ML-18 mechanisms have been remanufactured to ISO standards, including OEM recommendations and service advisories.
Safety First	Maintains existing maintenance and safety procedures; works with existing remote racking and switching equipment.
Repetitive Duty Upgrade	Need more than 3,000 operations? Ask about our Repetitive Duty Upgrade warranty.
Upgraded Pole Assemblies	New encapsulated pole assemblies are rugged, can extend existing interrupt capabilities, and have a longer service life than legacy pole designs.



MODELS & RATINGS

Identification				Rated Values						Related Required Capabilities		
				Voltage		Insulation Levels		Current				
						Rated Withstand Test Voltage			Short Circuit rms	Maximum	Closing and	
Replacement Tough Duty Part Number	Original Model Number	Normal rms Voltage Class (kV)	Normal 3-phase Class (MVA)	Rated Maximum Voltage (kV)	Rated Voltage Range Factor (K)	Low Frequency rms Voltage (kV)	Crest Impulse Voltage (kV)	Continuous rms Current Ratings (A)	Current Rating (at Rated Max kV) (kA)	Symmetrical Interrupting & 3-sec Short Time Capability Rating (kA)	Latching Capability rms Current (kA)	
VBTD-5-250-12	VB-4.16-250		750	4.76	1.24	19	60	1200	29	36	58	
VBTD-5-250-20	VB-4.10-250		250					2000				
VBTD-5-350-12	VB-4.16-350	4.16	350		1.19			1200	41	49	78	
VBTD-5-350-20	VB-4.10-350							2000				
VBTD-8-500-12	VB-7.2-500	7.2	7.3	500	8.25	1.25			1200	22	(1	66
VBTD-8-500-20	VB-7.2-500		.2 500	0.25	1.25	36	95	2000	33	41	00	
VBTD-15-500-12	VB-13.8-500		500		1.3			1200	18	23	37	
VBTD-15-500-20								2000				
VBTD-15-750-12	VB-13.8-750	13.8		50				1200	28	36	58	
VBTD-15-750-20			750					2000				

CircuitBreaker.com/ToughDuty









Contact your local
Group CBS Office or call (800) 232-5809.

